





RELIABLE. FLEXIBLE. FAST.









GET THE INDUSTRY'S LEADING HMI ENCLOSURES. BUILT TO YOUR SPECIFICATIONS IN AS LITTLE AS 2 WEEKS

Here are two new programs that put you in control. Rittal lets you choose the most popular components of our VIP and Optipanel HMI enclosure systems. Then we ship them to you in just 2 weeks from receipt of your purchase order. If you require more customization, such as non-standard sizes and accessories, or even your own front panel design, we can handle that too. We'll ship your completed, customized system in just 4 weeks.

2 Week Program

Simply choose the part number of the VIP or Optipanel from the selection charts. You can also indicate which standard pushbutton cutouts you require. That's it. Within just 2 weeks of receipt of your PO, your complete system is on its way.

4 Week Program

This option lets you choose the VIP or Optipanel components that fit your requirements from any of those listed in the appropriate selection charts. This means you can select from a broader range of enclosure dimensions and accessories for even greater flexibility. Plus, with this option you can submit your own front panel design.

TRIM COLORS TO ORDER COVER TRIM, END TRIM AVAILABLE IN FIVE COLORS. THE ENCLOSURE IN THE CHOSEN TRIM COLOR. CUST OMIZED COLORS CAN ALSO BE PR ODUCED FOR LARGER ORDERS.

WHICH SYSTEM IS RIGHT FOR YOU?

OPTIPANEL

The ideal combination of form, function and economy for smaller panels, Optipanel has a slender, sleek, flat design. The standard enclosure fits many commonly used front panels, and the system can be

customized to your exact requirements.


- Standard version provides 3.9" installation depth for typical front panels 7U H x 19" (482.5 mm) W
- Other available installation depths: 1.97" (50 mm), 3.97" (100 mm), and 5.90" (150 mm)
- Can be configured to your precise requirements with housing, mullion, rear wall and keyboard housing
- Operator housing can be subdivided to accept multiple panels
- Pendant arm supports available
- UL/cUL Type 12/IP 55 UL File Number: E76083

VIP

Rittal's VIP operator interface system is the industry's premier HMI enclosure solution. No other system provides this range of sizes, accessories and customization. With VIP you can



- Wide, narrow and combination frames to precisely match your application
- Installation depths from 6.10" (155 mm) through 17.28" (438 mm) for greater flexibility
- Keyboard housings that easily connect to the operator housing
- Available with or without heat dissipating cooling fins
- Operator housing can be subdivided to accept multiple panels
- UL/cUL Type 12/IP 55





RITTALXPRESS 2-WEEK OPTIPANEL PROGRAM

Rittal Xpress offers a comprehensive selection of enclosures and fully-assembled HMI enclosures in just two weeks from receipt of your order. Use the product selection guides on the following pages to create the code for your ideal HMI enclosure. A fax order form for enclosures with two-week availability is located on the next page of this brochure.

OPTIPANEL - CODE BOX 1 - SELECT YOUR HMI ENCLOSURE SIZE

Code	Part No.	Description	
Α	9970859	Optipanel, 7U H x 19" (482.5 mm) W x 6" (150 mm) D Without Connection	
В	9970860	Optipanel 7U H x 19" (482.5 mm) W x 6" (150 mm) D With Top Connection	
С	9970861	Optipanel 7U H x 19" (482.5 mm) W x 6" (150 mm) D With Bottom Connection	
D	9970862	Optipanel 7U H x 19" (482.5 mm) W x 6" (150 mm) D With Top & Bottom Connection	
E	9970863	Optipanel 10.5U H x 19" (482.5 mm) W x 6" (150 mm) D Without Connection	
F	9970864	4 Optipanel 10.5U H x 19" (482.5 mm) W x 6" (150 mm) D With Top Connection	
G	9970865	Optipanel 10.5U H x 19" (482.5 mm) W x 6" (150 mm) D With Bottom Connection	
Н	9970866	Optipanel 10.5U H x 19" (482.5 mm) W x 6" (150 mm) D With Top & Bottom Connection	







Connection at top



Connection at bottom




Connection top and bottom

OPTIPANEL - CODE BOX 2 - SELECT KEYBOARD OPTIONS

Code	Part No.	Description	
Y or N	9970867	Code Y or N: Keyboard for Optipanel, Preconfigured with Panel,	
		3.5U H x 19" (482.5 mm) W x 4" (100 mm) D	

Y = Yes keyboard is wanted N = No do not need



RITTAL XPRESS 2-WEEK OPTIPANEL Configuring HMI enclosures has never been easier. Log onto www.rittal.ca /rittalxpress/ and complete our real-time configurator. Or fill out the simple form below and fax it to 1-800-399-0748. _____Your Phone ___ Your Company_ _____Your Zip ___ Your E-mail __ _____ Your Account Number (if applicable) ___ Select your Optipanel enclosure size from options A-H on the opposite page and write the appropriate letter in the code box labeled 1. Select your keyboard option (Y = Yes keyboard is wanted, or N = No keyboard is required). Please write your selection in the code box labeled 2.Tell us about your cutouts. Please write the dimension for the cutout in the space provided. Please indicate the holes that you would like to activate by writing an A in each hole that will be 22.5 mm and B in each hole that will be 30.5 mm. **BUILD YOUR ENCLOSURE** CODE OPTIP ANEL — FINAL STEP — PANEL CUT OUT SIZE AND PUSHB UTT ONS REQUIRED 7U with Pushbuttons- Pleasewritetheheighandthewidthof 7U – Pleasewritetheheighandthewidthofthepanekutouan thepane but out in the space provide below Indicate the holes that thespaceprovide delow youwouldiketoactivateywritingan Ain eachholethatwillbe 22.5 mmandB in eachholethatwillbe30.5 mm. 483.0 +0.5 (19") ___ — 483.0 +0.5 (19") — Screen Height Screen Height_____ 310.3 +0.5 (7U) Screen Width_ Screen Width_ 311.2 +0.5 (7U) Unusable Panel Unusable Panel Space 10.5U - Pleasewritetheheighandthewidthofthepanekutout 10.5U with Pushbuttons- Pleasewritetheheighandthewidth of the pane but out in the space provide below Indicate he holes in the space provide below that you would ike to activat b ywritin q in A in each hole that will a constant of the property of thbe 22.5 mm and B in each hole that will be 30.5 mm. — 483.0 +0.5 (19°) — - 483.0 +0.5 (19°) -Screen Height_____ Screen Width_____ Screen Height____ 493.8 +0.5 (10.5U)493.8 +0.5 Screen Width_____ (10.5U)2 3 4 5 6 7 8 0000000

Unusable Panel Space

Unusable Panel Space



RITTALXPRESS 2-WEEK VIP PROGRAM

Rittal Xpress offers a comprehensive selection of enclosures and fully-assembled HMI enclosures in just two weeks from receipt of your order. Use the product selection guides on the following pages to create the code for your ideal HMI enclosure. A fax order form for enclosures with two-week availability is located on the next page of this brochure.

VIP - CODE BOX 1 - SELECT YOUR HMI ENCLOSURE SIZE

Code	Part No.	Description	
Α	9970870	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, Without Connection	
В	9970871	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top Connection	
С	9970872	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Bottom Connection	
D	9970873	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top & Bottom Connection	
Е	9970874	74 VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, Without Connection	
F	9970875	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top Connection	
G	9970876	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Bottom Connection	
Н	9970877	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top & Bottom Connection	
1	9970878	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, Without Connection, With Keyboard Connection	
J	9970879	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top Connection and Keyboard Connection	
K	9970880	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Bottom Connection and Keyboard Connection	
L	9970881	VIP 7U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top & Bottom Connection and Keyboard Connection	
M	9970882	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, Without Connection With Keyboard Connection	
N	9970883	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, Without Connection, With Keyboard Connection	
0	9970884	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Bottom Connection	
Р	9970885	VIP 10.5U H x 19" (482.5 mm) W x 7.3" 185 mm D, Including Cover Trims, With Top & Bottom Connection	



Without connection



Connection at top



Connection at bottom




Connection top and bottom



VIP - CODE BOX 2 - SELECT KEYBOARD OPTIONS


	Part No.	ode Part No.	Description	
	9970886	A 9970886 VIP Keyb	oard, 3.5U H x 19" (482.5 mm) W x 4.1" (105 mm) D	
		W	/ith an Adjustable Connection and FLEX-TUBE	
9970887 VIP Keyboard, 3.5U H x 19" (482.5 mm) W x 4.1" (105 mm) D		B 9970887 VIP Keyb	oard, 3.5U H x 19" (482.5 mm) W x 4.1" (105 mm) D	
			With an Adjustable Connection	
	_	C –	No Keyboard	
	_	C –	,	



RITT AL XPRESS 2 - W E E K VIP FORM Configuring HMI enclosures has never been easier. Log onto www.rittal.ca/rittalxpress/ and complete our real-time configurator. Or fill out the simple form below and fax it to 1-800-399-0748. Your Company_ _____ Your Phone ____ _____Your Zip ___ Your Name ___ _____ Your Account Number (if applicable) ___

Select your VIP enclosure size from options A-P on the opposite page and write the appropriate letter in the code box labeled 1. Select your keyboard from options A-C on the opposite page and write the appropriate letter in the code box labeled 2. Tell us about your cutouts. A. Write the dimensions for the screen in the space provided below.

BUILD YOUR ENCLOSURE CODE





4-WEEK OPTIPANEL PROGRAM RITTALXPRESS

Rittal Xpress is the easy way to create your ideal HMI with infinite configuration opportunities and have it delivered to your doorstep in just four weeks. Log onto www.rittal.ca/rittalxpress/HMI.cfm to fill out our real-time HMI configurator or work through pages 8 and 9 of this brochure to determine the dimensions and code configuration for your ideal Optipanel enclosure.

4-WEEK ORDERING IS THIS EASY!

Follow the steps below. Step 1-fill in the dimensions of your panel in inches. Step 2-choose your Design Options. Step 3-Build your customized part number, by inserting the product code numbers in the appropriate box. Step 4-Upload your drawings to our website.

STEP 1 - Panel Dimensions Required Fill in specificizein inches



000

_H x _____ D

STEP 2 - Design Options

A Installation Depth

Choose the depth you want and place its code number in the build your enclosure chart in the space labeled A.



50 mm (1.97")







150 mm (5.91")

B Operator Housing

Choose the operator housing you want and enter its code number in the build your own enclosure chart in the space labeled B.





1

1



With cross member

C Rear Wall


Choose the rear wall you want and enter its code number in the build your own enclosure chart in the space labeled C.



Rear panel screw fastened



Rear panel hinged on the longest edge.



Step 3, simply take the corresponding product code number by each of your selections in **Step 2** and place the numbers in the chart below. **Step 5**, fax the product code that you created by your selections in steps 2-4 along with your drawings to **1-800-477-4003**. Download our drawings from www.rittal-corp.com/rittalxpress/hmi and complete the drawings with your requirements. Submit the completed drawings along with your RFQ either online at **www.rittal-corp.com/rittalxpress/hmi** or fax to **1-800-477-4003**. Rittal will send a quote for your enclosure.



STEP 4 - CutOutSpecs

Download our drawings from **www.rittal-corp.com/rittalxpress/hmi** and complete the drawings with your requirements. Submit the completed drawings along with your RFQ either online at **www.rittal.carittalxpress/hmi.cfrm** or fax to **1-800-399-0748**.

000



4-WEEK VIP PROGRAM RITTALXPRESS

Rittal Xpress is the easy way to create your ideal HMI with infinite configuration opportunities and have it delivered to your doorstep in just four weeks. Log onto www.rittal.ca/rittalxpress/HMI.cfm to fill out our real-time HMI configurator or work through pages 10 - 13 of this brochure.

4-WEEK ORDERING IS THIS EASY!

Follow the steps below. Step 1-fill in the dimensions of your panel in inches. Step 2-choose your basic features. Step 3-select your Operator Housing. Step 4-select your Keyboard Housing. Step 5-fill in your build your enclosure code. Step 6-Upload your drawings to our website: www.rittal.ca/rittalxpress/HMI.cfm

STEP 1 - Panel Dimensions Required Fill in specificizein inches

000

H x _____ W x ____

STEP 2 - Basic Features

A Frame Style

Choose the frame style you want and place its code number in the build your enclosure chart in the space labeled A.







STEP 3 - OperatorHousing

B Installation Depth

Choose the depth you want and place its code number in the build your enclsure chart in the space labeled B.

Material:

Enclosure:

Extruded aluminum section Corner protectors: Plastic, self-extinguishing

Finish:

Enclosure: Natural anodized



Installation depth: 6.10" (155 mm)

1



Installation depth: 7.28" (185 mm)





000

Installation depth: 11.61" (295 mm)



Hinaed



7 Installation depth: 12.91" (328 mm)



9



Installation depth 17.24" (438 mm)

•••

C Front Design

Choose the front design you prefer and enter its code number in the build your own enclosure chart in the space labeled C.

Cross member

For horizontal and/or vertical division.

Material:

Extruded aluminum section, RAL 7035

Sealing bar

For horizontal and/or vertical division. The "slot-free" division produces a height gain of 1.10" (28 mm).


Material:

Extruded aluminum section 8 x 0.79" (20 mm), natural anodized

Adaptor plate

Material thickness

0.12" (3 mm) aluminum, natural anodized



Without cross member



With one cross member



With two cross members




With hinged front panel


D Cooling Fins

Choose the cooling fins you prefer and enter its code number in the build your own enclosure chart in the space labeled D.


Enclosures with an installation depth of 185 mm (7.28") and 328 mm (12.91") do not have any fins immediately behind the front frame at a depth of 44 mm (1.73"). The color of the corner protectors matches the trim color selected under section F.



No fins



Fins at sides




Continuous fins

3

E Trim Types

Choose the trim types you prefer and enter its code number in the build your own enclosure chart in the space labeled E.



Cover trim
To conceal the front panel assembly screws. For front panel thickness up to 3.5 mm (0.14").

1



End trim
Attractively finishes off the space between the front panel and the frame section. For all front panel thicknesses



Spacer trim
For installed equipment flush
with the frame section. For front
panel thickness up to approx.
3.5 mm (0.14").

F Trim Colors

Choose the trim color you prefer and enter its code number in the build your own enclosure chart in the space labeled F.



Turqoise (similar to RAL 5018)



Bright blue (similar to RAL 5005)



Bright red (similar to RAL 3001)



Pebble grey (similar to RAL 7030)



Graphite (similar to RAL 7024)

Note: Enclosure corner protectors are also supplied in the chosen color.

G Support Arm Connection – Choose the support arm connection you prefer and enter its code number in the build your own enclosure chart in the space labeled G.



Without connection



Connection, bottom



Connection, top




Connection, top and bottom, one cover plate included




H Mounting for Keyboard Housing

Choose the keyboard mounting you prefer and enter its code number in the build your own enclosure chart in the space labeled H.



Without connection to the keyboard housing



Connection to frame connector either fixed or adjustable

I Rear Panel

Choose the rear panel you prefer and enter its code number in the build your own enclosure chart in the space labeled I.



Screw fastened

Material:

Aluminum, natural anodized.

2

Hinged
For rapid service access

Material:

Aluminum, natural anodized.

J Keyboard Depth

Choose the keyboard depth you prefer and enter its code number in the build your own enclosure chart in the space labeled J.

Without fins.

For installing or positioning keyboards on top (with a depth of 1.06" (27 mm).

All keyboard housings are custom-produced to your dimensions. When selecting the wide front frame, the width of the keyboard housing depends on the operating housing.

Material:

Extruded aluminum section



Installation depth 1.73" (44 mm) for built-in keyboards



Installation depth 4.13" (105 mm) for built-in keyboards

K Trim Types

Choose the trim type you prefer and enter its code number in the build your own enclosure chart in the space labeled K.

Cannot be selected with keyboard housing depth 1.06" (27 mm) or support for keyboards.



Cover trim
To conceal the front panel assembly screws. For front panel thickness up to 0.14" (3.5 mm).



2

End trim
Attractively finishes off the space between the front panel and the frame section. For all front panel thicknesses.



Spacer trim
For installed equipment flush with the frame section. For front panel thickness up to approx. 0.14* (3.5 mm).

STEP 4 - KeyboardHousing

L Trim Colors

Choose the trim color you prefer and enter its code number in the build your own enclosure chart in the space labeled L.

Note: Enclosure corner protectors are also supplied in the chosen color.



Turqoise (similar to

RAL 5018)



RAL 5005)



(similar to

RAL 3001)



(similar to

RAL 7030)





Graphite (similar to RAL 7024)

M Keyboard Connector

Choose the keyboard connector you prefer and enter its code number in the build your own enclosure chart in the space labeled M.

Supplied loose with the keyboard housing for connecting operating housings and keyboard housings.

Material:

Die-cast zinc, RAL 7035



Frame connector, (fixed)



Frame connector, (adjustable)

N Cable Tube

Choose the cable tube you prefer and enter its code number in the build your own enclosure chart in the space labeled N.

Supplied loose with the keyboard housing for connecting operating housings and keyboard housings.

Material:

Die-cast zinc, RAL 7035



Without cable tube



Cable tube, rigid



Cable tube, flexible

Step 5, simply take the corresponding product code number by each of your selections in **Steps 3 & 4** and place the numbers in the chart below. **Step 6**: Log onto **www.rittal.ca/rittalxpress/hmi.cfm** to download our drawings. Make your changes to our drawings and submit the complete drawings along with your RFQ either online at **www.rittal.ca/rittalxpress/hmi.cfm** or fax to **1-800-399-0748** Rittal will send a quote for your enclosure. Rittal will send a quote for your enclosure.

Step 5 - BUILD YOUR ENCLOSURE CODE

































000

000

Height

x Width

x Depth

Panel Dimension in inches

STEP 6 - CutOutSpecs

Log onto www.rittal.ca/rittalxpress/hmi.cfm to download our drawings. Make your changes to our drawings and submit the complete drawings along with your RFQ either online at www.rittal.ca/rittalxpress/hmi.cfm or fax to 1-800-399-0748. Rittal will send a quote for your enclosure.

Rittal HMI Solutions



Industrial Enclosures



Wallmount Enclosures



System Climate Control



Power Distribution



IT Solutions



HMI Enclosures

Rittal Systems Ltd. • 7320 Pacific Circle • Mississauga, Ontario • L5T 1V1 • Canada Phone: (905) 795-0777 • Fax: (905) 795-9548 • Toll-free: 1-800-399-0748 www.rittal.ca • Email: rittal.systems@rittal.ca

Rittal Corporation • One Rittal Place • Springfield, OH • 45504 • USA Phone: (937) 399-0500 • Fax: (937) 390-5599 • Toll-free: 1-800-477-4000 www.rittal-corp.com • Email: rittal@rittal-corp.com

